

Mini sauterelle avec détecteur électro-magnétique

Référence Forme A	Référence Forme B	Taille	Force de ser- rage N	Force de rete- nue N	B ₁	B ₂	B ₃	B ₄	B ₅	B ₆	B ₇	B ₈	B ₉	B ₁₀	B ₁₁	B ₁₂	B ₁₃	B ₁₄
05650-050011	05650-050012	2	160	500	26	32	26	15	62	14	18	12	2,5	2,5	5	7	12	2
05650-090011	05650-090012	3	250	900	30	39	30	18	75	17	22	15	3,0	3,0	6	8	16	3
05650-100011	05650-100012	4	330	1000	35	45	35	22	93	20	25	18	4,0	4,0	6	8	18	4

Taille	D ₁	L ₁	L ₂	L ₃	L ₄ +0,1	L ₅	L ₆ ±0,1	L ₇	L ₈	L ₉ ±0,1	L ₁₀	L ₁₁	L ₁₂	L ₁₃	L ₁₄	⊞ kg
2	M5	123,0	96,0	27,5	20	7,5	10	14	5	16	10	50	57	16,0	12,0	0,300
3	G½	157,5	119,5	40,0	25	14,0	15	20	5	20	12	60	69	22,0	15,0	0,500
4	G¾	181,5	135,5	47,0	28	17,0	18	20	5	25	16	75	80	23,5	17,5	0,800

Mini sauterelle avec détecteur pneumatique

Référence Forme A	Référence Forme B	Taille	Force de ser- rage N	Force de rete- nue N	B ₁	B ₂	B ₃	B ₄	B ₅	B ₆	B ₇	B ₈	B ₉	B ₁₀	B ₁₁	B ₁₂	B ₁₃	B ₁₄
05650-050021	05650-050022	2	160	500	26	32	26	15	62	14	18	12	2,5	2,5	5	7	12	2
05650-090021	05650-090022	3	250	900	30	39	30	18	75	17	22	15	3,0	3,0	6	8	16	3
05650-100021	05650-100022	4	330	1000	35	45	35	22	93	20	25	18	4,0	4,0	6	8	18	4

Taille	D ₁	L ₁	L ₂	L ₃	L ₄ +0,1	L ₅	L ₆ ±0,1	L ₇	L ₈	L ₉ ±0,1	L ₁₀	L ₁₁	L ₁₂	L ₁₃	L ₁₄	⊞ kg
2	M5	123,0	96,0	27,5	20	7,5	10	14	5	16	10	50	57	16,0	12,0	0,300
3	G½	157,5	119,5	40,0	25	14,0	15	20	5	20	12	60	69	22,0	15,0	0,500
4	G¾	181,5	135,5	47,0	28	17,0	18	20	5	25	16	75	80	23,5	17,5	0,800

Mini sauterelle sans butée

Référence Forme A	Référence Forme B	Taille	Force de ser- rage N	Force de rete- nue N	B ₁	B ₂	B ₃	B ₄	B ₅	B ₆	B ₇	B ₈	B ₉	B ₁₀	B ₁₁	B ₁₂	B ₁₃	B ₁₄
05650-050041	05650-050042	2	160	500	26	32	26	15	62	14	18	12	2,5	2,5	5	7	12	2
05650-090041	05650-090042	3	250	900	30	39	30	18	75	17	22	15	3,0	3,0	6	8	16	3
05650-100041	05650-100042	4	330	1000	35	45	35	22	93	20	25	18	4,0	4,0	6	8	18	4

Taille	D ₁	L ₁	L ₂	L ₃	L ₄ +0,1	L ₅	L ₆ ±0,1	L ₇	L ₈	L ₉ ±0,1	L ₁₀	L ₁₁	L ₁₂	L ₁₃	L ₁₄	⊞ kg
2	M5	123,0	96,0	27,5	20	7,5	10	14	5	16	10	50	57	16,0	12,0	0,300
3	G½	157,5	119,5	40,0	25	14,0	15	20	5	20	12	60	69	22,0	15,0	0,500
4	G¾	181,5	135,5	47,0	28	17,0	18	20	5	25	16	75	80	23,5	17,5	0,800